



EBPP-20/40 POWER PACK MODULE FOR FLUORESCENT LIGHT FITTING / T5 LIGHT FITTING

Technical Data

Mode of Operation	: Maintained / Non-Maintained.
Input Voltage	: 240V \pm 10%, 50Hz
Battery	: Hi-Temp. Nickel Cadmium Battery.
Charging Current	: 130mA (Nominal).
Lamp Used	: 20 to 40 Watt Fluorescent Tube / PLL Tube (Please Refer to Supplier).
Operating Temperature	: 0°C to 60°C
Charger	: Solid-State Electronics Provide High Reliability with Trickle Charge-Facility.
Indication	: Red L.E.D. "On" Indicates Charging. Push Test-Switch to Simulate Power Failure (Optional).
Backup Time	: 3 Hours Duration.
Construction	: Electro-Galvanised Steel Casing of High Reflectance Finished with Corrosion Resistant Epoxy Spray Coating.
Weight	: \pm 0.2kg (Excluding Batteries).
#Warranty	: 5 Years.
Compliance	: Malaysia Standards MS-619, IP-20.
Protection	: Low-Voltage Cut-Off to Prevent Over-Discharge of Battery.

Dimension in mm
Tolerance: \pm 0.03 mm
Recessed Mounting

